



Glason - The Better Way of Doing Things!

Glason Oven & Grill Cleaner

MATERIAL SAFETY DATA SHEET

Hazardous according to the criteria of NOHSC Australia.

I IDENTIFICATION

Product Name: Glason Oven and Grill

Other Names: Proper Shipping Name is CAUSTIC ALKALI LIQUID, N.O.S.

Product Code: None.

UN No: 1719

Hazchem Code: 2R

Dangerous Goods Class: 8 Corrosive Substances.

Sub Risk Class: None allocated.

Packaging Group: II

Most EPGs may now be substituted by the Initial Emergency Response Guide, available from Standards Australia.

Poison Schedule: Not scheduled.

Chemical Family: Water solution of ingredients (see below).

Uses: Domestic and industrial oven cleaner.

Physical Appearance & Properties

Appearance & Odour: Red liquid. Mild odour.

Melting/softening point: Approximately 0°C.

Boiling point and vapour pressure: Approximately 100°C at 100kPa.

Volatile materials: Water component.

Flashpoint: Does not burn.

Flammability limits: Not applicable. This product does not burn.

Specific gravity: Not available.

Solubility in water: Completely soluble.

Corrosiveness: Very corrosive

Vapour Pressure: 18mm Hg at 20°C (water vapour pressure).

Ingredients	CAS No	Proportion, %	Worksafe Exposure Limits	
Chemical Entity			TWA, mg/m ³	STEL, mg/m ³
Potassium hydroxide	1310-58-3	10	2	Peak
Other non hazardous ingredients	secret	1-3	not set	not set
Water	7732-18-5	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

II HEALTH HAZARD DATA

Health Effects:

No specific data is available for the product for chronic exposure symptoms. The ingredients are not listed as carcinogenic in Worksafe's document "Exposure Standards for Atmospheric Contaminants in the Occupational Environment" (May 1995), nor in NOHSC's "List of Designated Hazardous Substances" (April 1999).

Acute Effects:

Swallowed: Data suggests that this product is corrosive to the gastrointestinal tract. Will cause burning to mouth and throat, possible irreversible problems, even death unless treated promptly.

Eye: This product is very corrosive to the eyes. It will quickly cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is quickly treated, permanent blindness and facial scarring will occur.

Skin: This product is corrosive to skin. It will cause effects such as severe itchiness, blistering and skin reddening and death of skin tissues. Exposure may lead to permanent damage including scarring.

Inhalation: Data indicates that this product is irritating if inhaled. Will cause discomfort to throat and lungs and/or coughing which should disappear once exposure has ceased.

Product: OVEN AND GRILL

Issued by: Glason Specialised Services Pty Ltd
Phone: (02)4323 7792

Issued: May, 2010
Page 1 of 4

MATERIAL SAFETY DATA SHEET

First Aid:

Eyebaths or eyewash stations and safety deluge showers should be provided where this product is being used. If poisoning occurs, contact a Doctor or Poisons Information Centre. Phone 13 1126 from anywhere in Australia. If possible have this MSDS or product label with you.

Swallowed: If swallowed, do NOT induce vomiting. Wash mouth with water and give a glass of water to drink. Seek medical attention.

Eyes: If this product comes into contact with eyes, hold open and wash with running water for at least 15 minutes. Do not try to remove contact lenses unless trained. Seek immediate medical attention.

Skin: If product gets on skin, immediately remove contaminated clothing and wash skin with soap and running water for at least 15 minutes. Seek immediate medical attention if skin blisters, or if it looks or feels unusual. If safety shower is available, use it promptly. If you have the time and resources, see if you can neutralise the corrosive medium, especially if on face, in eyes or in/on other sensitive areas.

Inhalation: If vapours or mists have been inhaled, and irritation or unusual symptoms have developed, remove to fresh air and observe until recovered. If irritation or symptoms persists more than about 30 minutes, seek medical advice.

Advice to Doctor: Treat symptomatically. Note the nature of this product.

III PRECAUTIONS FOR USE

Risk Phrases are: R34, R37, R41. Causes burns. Irritating to respiratory system. Risk of serious damage to eyes.

Exposure Standards:

A time weighted average (TWA) has been established for Potassium hydroxide, present in significant quantities in this product. This value is 2mg/m³. The corresponding STEL level is "Peak". The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The exposure value at the TWA is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. See ingredients section on page 1 of this data sheet. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Engineering Controls:

In industrial situations, concentration values below the TWA value should be maintained. Values may be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify the process or environment to reduce the problem.

Personal Protection:

Respiratory Protection: If there is a significant chance of dusts, vapours or mists accumulating in the area where this product is being used, a mask or respirator should be used. For help in selecting equipment, consult AS/NZS 1715.

Protective Gloves: Impermeable protective gloves must be worn when you are using this product. Failure to do so will lead to burns to the skin, and likely scarring. All skin areas must be covered. For help in selecting suitable equipment, consult AS 2161.

Eye Protection: Protective eyewear must be worn when using this product. Coverage should extend to all facial areas. Eye contact will prove at best painful and will almost always cause irreversible damage and blindness, as well as scarring of face and other contacted tissues. Consult AS1336 and AS/NZS 1337 for advice on Industrial Eye Protection.

Clothing: Clean impermeable overalls or protective clothing should always be worn when handling this product, preferably with an apron. If contaminated, laundry should be advised of the nature of the contamination, or, preferably, clothing should be destroyed. Consult AS2919 for advice on Industrial Clothing.

Safety Boots: Wearing safety boots in industrial situations is advisory. Consult AS/NZS2210 for advice on Occupational Protective Footwear.

Always wash hands before smoking, eating or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Product: OVEN AND GRILL

Issued by: Glason Specialised Services Pty Ltd
Phone: (02)4323 7792

Issued: May, 2010
Page 2 of 4

MATERIAL SAFETY DATA SHEET

IV SAFE HANDLING INFORMATION

Safety Phrases are: S20, S23, S28, S36/37/39. When using, do not eat or drink. Do not breathe mists. After contact with skin, wash immediately with plenty of water. Wear suitable protective clothing, gloves and eye/face protection.

Storage & Transport

This product is classed as UN1719, Dangerous Goods Class 8 Corrosive Substances. Proper Shipping name is CAUSTIC ALKALI LIQUID, N.O.S. Class 8 Corrosive Substances shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances where the Toxic Substances are cyanides and the Corrosives are acids), 7 (Radioactive Substances), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Poisonous Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 6 (Toxic Substances except where the Toxic Substances are cyanides and the Corrosives are acids) and 9 (Miscellaneous Dangerous Goods). Not a Scheduled Poison. Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames, and make sure that the product does not come into contact with substances listed under "Materials to avoid" below.

Spills & Disposals

In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective chemically resistant clothing including face mask, face shield, gauntlets and self contained breathing apparatus. See above under Personal Protection regarding Australian Standards relating to personal protective equipment. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. Contaminated area may be neutralised by washing with weak or dilute acid. This material may be suitable for approved landfill. Dispose of only in accord with all regulations. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Fire & Explosion Hazard

There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Flashpoint: Does not burn.

Flammability limits: Not applicable. This product does not burn.

Extinguishing Media: This product does not burn. Use extinguishing media suited to the materials that are burning.

Water fog or fine spray is the preferred medium for large fires.

Special Fire Fighting procedures: If a significant quantity of this product is involved in a fire, call the fire brigade. When fighting fires involving significant quantities of this product, wear safety boots, non-flammable overalls, gloves, hat, goggles and respirator. All skin areas should be covered. Aim to dilute the material with large quantities of water. If practical, contain diluted material and prevent from entering drains and water courses.

Unusual Fire & Explosion Hazards: This product is unlikely to decompose at temperatures normally achieved in a fire. Likely to decompose only after heating to dryness followed by further strong heating.

Stability: This product is unlikely to spontaneously decompose.

Polymerisation: This product is unlikely to spontaneously polymerise.

Decomposition Products: No significant quantities of decomposition products are expected at temperatures normally achieved in a fire.

Materials to avoid: acids, zinc, tin, aluminium and their alloys.

Note: This product is classed as a Dangerous Good. We suggest you consult your state's Dangerous Goods laws in order to clarify your obligations regarding the storage of this product.

V OTHER INFORMATION

This MSDS is prepared in accord with the Worksafe Australia document "National Code of Practice for the Preparation of Material Safety Data Sheets", 1994.

Contact Points:

Product: OVEN AND GRILL

Issued by: Glason Specialised Services Pty Ltd
Phone: (02)4323 7792

Issued: May, 2010
Page 3 of 4

MATERIAL SAFETY DATA SHEET

Police and Fire Brigade:	Dial	000
If ineffective:	Dial	1100 (Exchange)
For emergency response:	Dial	(02)4323 7792
National Poisons Information Centre:	Dial 13 1126 (from anywhere in Australia)	

Please read all labels carefully before using product.

This MSDS copyright © Kilford & Kilford Pty Ltd, January, 2006.
<http://www.kilford.com.au> Phone (02)9516 2079

Product: OVEN AND GRILL

Issued by: Glason Specialised Services Pty Ltd
Phone: (02)4323 7792

Issued: May, 2010
Page 4 of 4